



January 1, 2005  
Supercedes 1/1/2004

**RS Multi-Purpose Hose Rubber**

**RS x Assembly M/M**

Item Number	Nom. I.D.	Nom. O.D.	Max W.P.	WT. Per Ft.	Assembly Length
A-RS0250RD100	1/4	0.490	300 PSI	.09 lbs	100 ft
A-RS0250RD50	1/4	0.490	300 PSI	.09 lbs	50 ft
A-RS0250RD25	1/4	0.490	300 PSI	.09 lbs	25 ft
A-RS0375RD100	3/8	0.670	300 PSI	.15 lbs	100 ft
A-RS0375RD50	3/8	0.670	300 PSI	.15 lbs	50 ft
A-RS0375RD25	3/8	0.670	300 PSI	.15 lbs	25 ft

**RS Multi-Purpose Hose Rubber**

**Quick-Coupler / Plug**

Item Number	Nom. I.D.	Nom. O.D.	Max W.P.	WT. Per Ft.	Assembly Length
A-RS0250RD100	1/4	0.490	300 PSI	.09 lbs	100 ft
A-RS0250RD50	1/4	0.490	300 PSI	.09 lbs	50 ft
A-RS0250RD25	1/4	0.490	300 PSI	.09 lbs	25 ft
A-RS0375RD100	3/8	0.670	300 PSI	.15 lbs	100 ft
A-RS0375RD50	3/8	0.670	300 PSI	.15 lbs	50 ft
A-RS0375RD25	3/8	0.670	300 PSI	.15 lbs	25 ft

\* Weight Per Foot does not include fittings.

\* For assemblies made with other coupling types, please contact **Sales & Marketing** at  
(800) 978-2667

**POTENTIAL USE:** Multi-purpose use including air, water (up to 200 F)  
Outstanding resistance to heat and ozone.

**TEMPERATURE:** -40 F (-40 C) to +200 F (+93 C) continuous service

**CONSTRUCTION:**  
**Tube:** EPDM  
**Reinforcement:** Synthetic High Tensile Textile Cord  
**Cover:** EPDM Red

**PACKAGING:** Coiled, tied and shrink-wrapped to pallet

**BRANDING:** "Flex-Tech RS Multi-Purpose - 3/8" ID 300 PSI W.P. Made in USA"

**TO PLACE AN ORDER:**

Use the above **Item Number** and add **two** letters for the desired **coupling** combination.

**(QC)** quick-coupler (includes 1/4" MPT each end) or **(MM)** male NPT.

**EX:** 3/8" x 50' (red cover) with male MPT each end would be ordered as: **ARS0375RD50MM.**