



January 1, 2005  
Supersedes 1/1/2004

**GS Multi-Purpose Hose PVC**

Flex **GS** x **REEL**

Item Number	Nom. I.D.	Nom. O.D.	Max W.P.	WT. Per Ft.	Std Pkg Qty
GS-0250__-RL	1/4	0.500	300 PSI	.095 lbs	500 ft
GS-0375__-RL	3/8	0.595	300 PSI	.105 lbs	500 ft
GS-0500__-RL	1/2	0.785	300 PSI	.165 lbs	500 ft

**GS Multi-Purpose Hose PVC**

Flex **GS** x **COIL**

Item Number	Nom. I.D.	Nom. O.D.	Max W.P.	WT. Per Ft.	Std Pkg Qty
GS-0250__-00	1/4	0.500	300 PSI	.095 lbs	500 ft
GS-0375__-00	3/8	0.595	300 PSI	.105 lbs	500 ft
GS-0500__-00	1/2	0.785	300 PSI	.165 lbs	300 ft

**POTENTIAL USE:** Multipurpose applications including air, water (up to 150 F) pneumatic hand tools, air service for painting equipment, coolant lines etc...

**FEATURES:**

- \* U.V. and Ozone Resistant
- \* Non-Marking Cover
- \* Lightweight
- \* Long Continuous Lengths
- \* Silicone Free Tube & Cover
- \* Chemical Resistance of PVC
- \* Meets RMA (Class B) Oil Resistance for Tube & Cover

**TEMPERATURE:** -15 F (-26 C) to +150 F (+65 C) continuous service

**CONSTRUCTION:**  
**Tube:** Specially Formulated, PVC Compound  
**Reinforcement:** High Tensile Strength Textile Cord  
**Cover:** Specially Formulated, PVC Compound available in:

**STANDARD COLORS:** red (**RD**), dk-blue (**BLD**), lt-blue (**BLL**), yellow (**YW**)

**CALL FOR AVAILABILITY:** safety-orange (**OR**) and gray (**GY**), lt-blue (**BLL**)

**BRANDING:** "Flex-Tech GS Multi-Purpose - 3/8" ID 300 PSI W.P. (2.1 Mpa) - Made in USA"

**TO PLACE AN ORDER:**

Use the above **Item Number** and appropriate letters for **color** choice in the blank space indicated. **EX:** A reel of 3/8" Flex GS with **Red** cover would be ordered as: **GS-0375RD-RL**