



January 1, 2005  
Supersedes 1/1/2004

**GS Multi-Purpose Hose PVC**

**GS x Assembly M/M**

Item Number	Nom. I.D.	Nom. O.D.	Max W.P.	WT. Per Ft.	Assembly Length
A-GS-0250__ 25MM	1/4	0.500	300 PSI	.095 lbs	25 ft
A-GS-0250__ 50MM	1/4	0.500	300 PSI	.095 lbs	50 ft
A-GS-0250__ 100MM	1/4	0.500	300 PSI	.095 lbs	100 ft
A-GS-0375__ 25MM	3/8	0.595	300 PSI	.105 lbs	25 ft
A-GS-0375__ 50MM	3/8	0.595	300 PSI	.105 lbs	50 ft
A-GS-0375__ 100MM	3/8	0.595	300 PSI	.105 lbs	100 ft
A-GS-0500__ 25MM	1/2	0.785	300 PSI	.165 lbs	25 ft
A-GS-0500__ 50MM	1/2	0.785	300 PSI	.165 lbs	50 ft
A-GS-0500__ 100MM	1/2	0.785	300 PSI	.165 lbs	100 ft

\* 1/2" GS assemblies made with 3/8" MPT as standard. For 1/2" MPT add \$ .98 to net.

**GS Multi-Purpose Hose PVC**

**Quick-Coupler / Plug**

Item Number	Nom. I.D.	Nom. O.D.	Max W.P.	WT. Per Ft.	Assembly Length
A-GS-0250__ 25QP	1/4	0.500	300 PSI	.095 lbs	25 ft
A-GS-0250__ 50QP	1/4	0.500	300 PSI	.095 lbs	50 ft
A-GS-0250__ 100QP	1/4	0.500	300 PSI	.095 lbs	100 ft
A-GS-0375__ 25QP	3/8	0.595	300 PSI	.105 lbs	25 ft
A-GS-0375__ 50QP	3/8	0.595	300 PSI	.105 lbs	50 ft
A-GS-0375__ 100QP	3/8	0.595	300 PSI	.105 lbs	100 ft

\* 300 PSI (2.1 Mpa) at 70 F (21 C), 250 PSI (.72 Mpa) at 150 F (+66 C).

\* Weight Per Foot does not include fittings.

\* **Strain Relief(s) / Bend Restrictor(s)** are available and may be added to assemblies at a Net (\$) increase per assembly based on the following: (1/4" & 3/8") Add \$.25 per SR. Add \$.28 per SR for (1/2").

**PACKAGING:** Coiled, tied and shrink-wrapped to pallet

**BRANDING:** Flex-Tech GS Multi-Purpose - 3/8" ID 300 PSI W.P.(2.1 Mpa) Made in USA

**TO PLACE AN ORDER:**

Use the above **Item Number** and appropriate letters for **color** choice in the blank space at the end of the Item Number. The **last two item number** characters designate choice of fittings.

**EX:** 3/8" x 100' w/ 1/4" MM with Dk-Blue cover would be ordered as: **AGS0375BLD100MM**