



January 1, 2005
Supersedes 1/1/2004

RT Multi-Purpose Hose
Rubberized Thermoplastic
Flex RT x Assembly M/M

Item Number	Nom. I.D.	Nom. O.D.	Max W.P.	WT. Per Ft.	Assembly Length
A-RT-0250__ 25MM	1/4	0.500	300 PSI	.095 lbs	25 ft
A-RT-0250__ 50MM	1/4	0.500	300 PSI	.095 lbs	50 ft
A-RT-0250__ 100MM	1/4	0.500	300 PSI	.095 lbs	100 ft
A-RT-0375__ 25MM	3/8	0.595	300 PSI	.105 lbs	25 ft
A-RT-0375__ 50MM	3/8	0.595	300 PSI	.105 lbs	50 ft
A-RT-0375__ 100MM	3/8	0.595	300 PSI	.105 lbs	100 ft
A-RT-0500__ 25MM	1/2	0.785	300 PSI	.165 lbs	25 ft
A-RT-0500__ 50MM	1/2	0.785	300 PSI	.165 lbs	50 ft
A-RT-0500__ 100MM	1/2	0.785	300 PSI	.165 lbs	100 ft

* 1/2" RT assemblies made with 3/8" MPT as standard. For 1/2" MPT add \$.98 to net.

RT Multi-Purpose Hose
Rubberized Thermoplastic
Quick-Coupler / Plug

Item Number	Nom. I.D.	Nom. O.D.	Max W.P.	WT. Per Ft.	Assembly Length
A-RT-0250__ 25QP	1/4	0.500	300 PSI	.095 lbs	25 ft
A-RT-0250__ 50QP	1/4	0.500	300 PSI	.095 lbs	50 ft
A-RT-0250__ 100QP	1/4	0.500	300 PSI	.095 lbs	100 ft
A-RT-0375__ 25QP	3/8	0.595	300 PSI	.105 lbs	25 ft
A-RT-0375__ 50QP	3/8	0.595	300 PSI	.105 lbs	50 ft
A-RT-0375__ 100QP	3/8	0.595	300 PSI	.105 lbs	100 ft

* 300 PSI (2.1 Mpa) at 70 F (21 C), 250 PSI (.72 Mpa) at 150 F (+66 C).

* Weight Per Foot does not include fittings.

* **Strain Relief(s) / Bend Restrictor(s)** are available and may be added to assemblies at a Net (\$) increase per assembly based on the following: (1/4" & 3/8") Add \$.25 per SR. Add \$.28 per SR for (1/2").

STANDARD COLORS: red (RD), blue (BL) and yellow (YW)

BRANDING: Flex-Tech RT Multi-Purpose - 3/8" ID 300 PSI W.P. (2.1 Mpa) Made in USA

TO PLACE AN ORDER:

Use the above **Item Number** and appropriate letters for **color** choice in the blank space at the end of the Item Number. The **last two item number** characters designate choice of fittings.

EX: 1/4" x 50' w/ QC & Plug and Blue cover would be ordered as: **ART0250BL50QP**