FLEX-TECH
HOSE & TUBING, INC.

January 1, 2005
Supersedes 1/1/2004

**RTW - Industrial Grade Water Hose** ***Rubberized* Thermoplastic** **Assembly**

| Item Number | Nom. I.D. | Nom. O.D. | Max W.P. | WT. Per Ft. | Assembly Length |
|---|---|---|---|---|---|
| ARTW-0625RD100MF | 5/8 | 0.890 | 175 PSI | .185 lbs. | 100 ft. |
| ARTW-0625RD75MF | 5/8 | 0.890 | 175 PSI | .185 lbs. | 75 ft. |
| ARTW-0625RD50MF | 5/8 | 0.890 | 175 PSI | .185 lbs. | 50 ft. |
| ARTW-0625RD25MF | 5/8 | 0.890 | 175 PSI | .185 lbs. | 25 ft. |
| ARTW-0750RD100MF | 3/4 | 1.060 | 175 PSI | .270 lbs. | 100 ft. |
| ARTW-0750RD75MF | 3/4 | 1.060 | 175 PSI | .270 lbs. | 75 ft. |
| ARTW-0750RD50MF | 3/4 | 1.060 | 175 PSI | .270 lbs. | 50 ft. |
| ARTW-0750RD25MF | 3/4 | 1.060 | 175 PSI | .270 lbs. | 25 ft. |

**RTW - Industrial Grade Water Hose** ***Rubberized* Thermoplastic** **Reel**

| Item Number | Nom. I.D. | Nom. O.D. | Max W.P. | WT. Per Ft. | Std Pkg Qty |
|---|---|---|---|---|---|
| RTW-0625RD-RL | 5/8 | 0.890 | 175 PSI | .185 lbs. | 500 ft. |
| RTW-0750RD-RL | 3/4 | 1.060 | 175 PSI | .270 lbs. | 600 ft. |

* Working pressure decreases as temperature increases.
* Weight Per Foot does not include fittings at each end.

**POTENTIAL USE:**

* Heavy-duty Commercial & Construction Use
* General Water Service in Industrial Plants
* Municipal Maintenance and Park Departments
* Irrigation Supply Lines
* Heavy-duty Washdown
* Farm / Ranch Maintenance

**FEATURES:**

* RMA Class B Oil Resistance.
* *Rubberized* Thermoplastic for enhanced flexibility.
* Exceptional Abrasion Resistant Cover.
* Excellent Resistance to Weather & Aging.
* Available in Assembly or Bulk Form.
* Heavy-duty Fittings on Each Assembly.

**TEMPERATURE:**

**+15 F** (1.7 C) to **+150 F** (+65 C)

**CONSTRUCTION:**

* Tube: Specially Formulated PVC
* Reinforcement: High Tensile Strength Textile Cord
* Cover: (**Red**) Specially Formulated PVC

**BRANDING:**

**"Flex-Tech RTW Industrial Grade Water Hose - 5/8" I.D.**

1100 Civic Center Loop San Marcos, TX 78666
Phone: (800) 978-2667 Fax: (512) 558-2492
www.flex-tech-hose.com