

PW 61 - Potable Water Hose

NSF-61

COIL

Item Number	Nom. I.D.	Nom. O.D.	Max W.P.	WT. Per Ft.	Std Lengths Pkg Qtys	List Price \$ Per Foot
PW-0250CW-00	1/4	0.475	300 PSI	0.069 lbs	500 / 100 ft	0.335
PW-0313CW-00	0.31	0.531	300 PSI	0.080 lbs	500 / 100 ft	0.388
PW-0375CW-00	3/8	0.595	300 PSI	0.098 lbs	500 / 100 ft	0.462
PW-0500CW-00	1/2	0.750	300 PSI	0.140 lbs	300 / 100 ft	0.625
PW-0625CW-00	0.63	0.895	200 PSI	0.180 lbs	200 / 100 ft	0.795
PW-0750CW-00	0.75	1.045	150 PSI	0.215 lbs	200 / 100 ft	1.080
PW-1000CW-00	1	1.315	150 PSI	0.315 lbs	200 / 100 ft	1.410

Use - 100 instead of -00 when ordering 100' cut lengths.

SF = (3:1)

POTENTIAL USE:

- * Domestic hot and cold water applications.
- * Drinking water applications.

FEATURES:



CERTIFIED TO
ANSI/NSF-61

- * **NSF-61 Certified Hose**
drinking water system components.
- * Constructed of PVC materials sanctioned for food contact use under CFR title 21, parts 170-199.
- * Material compounds contain no substances designated as hazardous under California **Proposition 65**.
- * Non-Marking
- * White Tube & Clear Cover
- * Ozone Resistant
- * Light-weight
- * When coupled properly, 1/4"-1/2" sizes will conform to high-temp extreme test requirements as defined by ASME A112.18.6, Section 4.3

TEMPERATURE:

14 F (+4 C) TO 140 F (+65 C) continuous service

CONSTRUCTION:

Tube: White PVC compound, specially formulated in compliance with applicable FDA regulations, NSF standard 61 and California Proposition 65.

Reinforcement: High Tensile Strength Textile Cord

Cover: Clear PVC compound, specially formulated in compliance with applicable FDA regulations, NSF standard 61 and California Proposition 65.

PACKAGING:

Coiled, tied and individually bagged in heavy-duty, clear plastic bag.

BRANDING:

None